

Best practices for DWA-131 working on D-Link Smart Series DVRs.

1. Make sure that the DWA-131 is always connected to the **Backside Lower USB port** on the DVR.
2. If the DVR was earlier connected to a wired network, please make sure to **disconnect the LAN cable**.
3. Make sure that the **LAN cable is kept disconnected when DWA-131 is connected**.
4. Access the **DVR interface on the Monitor** connected to DVR over VGA/HDMI.
5. **Factory Reset the DVR** to reset network settings. (Main menu >> Settings >> Config >> Resetting).
6. Before detecting & connecting to any wifi network, make sure that
 - Wifi SSID does not have a **SPACE** in between.
 - **No Special Character** (@/\$/#/%) is used in Wifi Password.
 - **WPA2-PSK AES** is the Wifi security preferred and recommended.
 - Make sure **DHCP is enabled** on the router/Jiofi device.
7. Procedure to connect to wifi.
 - Enable Wifi and click on Apply.
 - Search for Wifi networks and enter password for same and click on Apply.

Please note:

- It is not recommended, to connect DWA-131 and LAN cable simultaneously as, DVR does not support Simultaneous Dual Network Interfaces.
- Also, after clicking on Apply after entering Wifi Password, navigate to a different page and revert to Wifi page to check if Status is Connected & IP address is updated.