

DVR-F2108-L1H5

8CH H.265+ 2MP Lite DVR



KEY FEATURES

- Supports 8CH, 1SATA
- Support AHD/TVI/CVI/IP cameras up to 2MP
- Support H.264/H.264+/H.265/H.265+
- Supports Tamper & Video Loss Detection
- Support 3G/4G Wi-Fi
- Support Cloud storage

DVR-F2108-L1H5

8CH, H.265+ 2MP Lite DVR

INTERFACE



SPECIFICATION

VIDEO & AUDIO INPUT

Video Input	8ch BNC interface (1.0Vp-p, 75 Ω)
TVI / CVI /AHD	1080P, 720P
IPC	Up to 8ch Resolution up to 2MP
Audio Input	1-ch RCA (2.0 Vp-p, 1 KΩ)
Two way Talk	1-ch multiplex with Audio Input (RCA)

VIDEO & AUDIO OUTPUT

HDMI	1ch, resolution: 1920×1080/60Hz, 1280×1024/60Hz, 1280×720/60Hz 1024×768/60Hz
VGA	1ch, resolution: 1920×1080/60Hz, 1280×1024/60Hz, 1280×720/60Hz 1024×768/60Hz
CVBS output	NA
Audio Output	1-ch RCA (Linear, 1kΩ)

RECORDING

Compression	H.264/H.264+/H.265/H.265+
Resolution	8ch 1080P Lite@15fps; 960H1/D1/CIF real time
Frame Rate(fps)	1fps-15fps
Video Bit Rate	11Kbps-2707Kbps
Record Mode	Manual, Schedule, Alarm
Audio Compression	G.711a
Audio Bit Rate	64Kbps

PLAYBACK & BACKUP

Playback Mode	Normal/Time Division/ Label/ Event/ Picture Playback
Playback Rate	4ch Playback
Backup Mode	USB Device/Network

CLOUD FUNCTION

Cloud Storage	Support
Cloud Upgrade	Support

NETWORK

Ethernet	1 RJ-45 10/100 Mbps self-adaptive Ethernet interface
Network Function	HTTPs, HTTP, TCP/IP, IPv4, UPnP, Onvif2.6, RTSP, RTCP, UDP, SMTP, IGMP, NTP, DHCP, DNS, DDNS, FTP, P2P
Smart Phone	IOS (iPhone, iPad), Android (Phone, Pad)

HARD DISK	
SATA	1 HDD
Capacity	Up to 6TB capacity for each HDD
EXTERNAL INTERFACE	
Serial Interface	NA
USB Interface	2 × USB 2.0
GENERAL	
Power Supply	DC12V, 1.5A
Power Consumption	≤15W(without HDD)
Working Environment	-10°C~+55°C / 10%~90%RH
Dimension (W×D×H)	250 x 230 x 45mm
Weight (without HDD)	1.5kg
Certification	CE, BIS
SYSTEM MANAGEMENT	
Mobile Software	D-Link Smart Plus CCTV App
Desktop Software	D-Link Smart Video Surveillance 2.0
System Requirement for Web Interface	IE