

DVR-F2108-L2

8CH, 5MP Lite DVR



KEY FEATURES

- Support AHD/TVI/CVI/IP Cameras
- Support AHD/TVI cameras up to 5MP
- Support H.265+/H.265
- Support Time Division & Instant Playback
- Support Cloud storage
- Support Event stream

INTERFACE



SPECIFICATION

VIDEO & AUDIO INPUT

Video Input	8ch BNC interface(1.0Vp-p, 75 Ω)
TVI	5MP,4MP,1080P, 720P
CVI	4MP,1080P, 720P
AHD	5MP,4MP,1080P, 720P
IPC	Up to 8ch Up to 5MP in full IP mode
Audio Input	1-ch, multiplex with Audio Input(RCA)
Two way talk	1-ch, multiplex with Audio Input(RCA)

VIDEO & AUDIO OUTPUT

HDMI	1ch, resolution: 4K, 1920×1080/60Hz,1280×1024/60Hz,1280×720/60Hz
VGA	1ch, resolution: 1920×1080/60Hz, 1280×1024/60Hz, 1280×720/60Hz
CVBS output	1-ch,BNC(1.0Vp-p,75Ω),resolution:PAL:704x576,NTSC:704x480
Audio Output	1-ch, RCA (Linear, 1kΩ)

RECORDING

Compression	H.265/H.265+
Resolution	8ch 5MP Lite@12fps; 8ch 4MP Lite/1080P@15fps; 1080P Lite@25fps 720P/960H/D1/CIF real time
Video Bit Rate	11Kbps-4096Kbps
Audio Compression	G.711a
Audio Bit Rate	64kbps

PLAYBACK & BACKUP

Playback Mode	Normal/Time Division/ Label/ Event/ Picture Playback
Playback Rate	4ch Playback
Backup Mode	USB Device/Network

CLOUD FUNCTION

Cloud Storage	Support
Cloud Upgrade	Support

NETWORK

Ethernet	1 RJ-45 10 /100 Mbps self-adaptive Ethernet interface
Network Function	HTTPs, HTTP,TCP/IP,IPv4,UPnP,Onvif 2.6,RTSP,RTCP, UDP, SMTP,IGMP,NTP, DHCP,DNS,DDNS, FTP, P2P
Smart Phone	IOS(iPhone, iPad), Android(Phone, Pad)

HARD DISK	
SATA	1 HDD
Capacity	Up to 8TB capacity for each HDD
EXTERNAL INTERFACE	
Serial Interface	NA
USB Interface	2 × USB 2.0
GENERAL	
Power Supply	DC12V, 1.5A
Power Consumption	≤15W(without HDD)
Working Environment	-10°C~+55°C / 10%~90%RH
Dimension (W×D×H)	250 x 230 x 45mm
Weight (without HDD)	1.5kg
Certification	CE, BIS
SYSTEM MANAGEMENT	
Mobile Software	D-Link Smart Plus CCTV App
Desktop Software	D-Link Smart Video Surveillance 2.0
System Requirement for Web Interface	IE